

Safety Data Sheet
PREP-A-LUBE II

SECTION I - IDENTIFICATION

PRODUCT IDENTIFIER: PREP-A-LUBE II
PRODUCT CODE: 5405
RECOMMENDED USE: High Pressure, Red Spray Grease
RESTRICTIONS ON USE: None known.
COMPANY NAME: ATCO International
COMPANY ADDRESS: 1401 Barclay Circle; Marietta, GA 30060
COMPANY PHONE: 800-723-2826 / 770-424-7550
EMERGENCY PHONE: 800-255-3924 (ChemTel / VelocityEHS, 24 hours a day/ 7 days a week)

SECTION II – HAZARDS IDENTIFICATION

CLASSIFICATION: Flammable Aerosol: Category 1
Gases Under Pressure: Liquefied Gas
Skin Irritant: Category 2
Specific Target Organ Toxicity (Single Exposure): Category 3
Aspiration Hazard: Category 1

HAZARD STATEMENT(S): DANGER: Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways.

This product contains the following percentage of chemicals of unknown toxicity: N/A

PRECAUTIONARY STATEMENTS: Keep away from heat, sparks, open flames, and hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Store in a well-ventilated place. Wash hands thoroughly after handling. Wear protective gloves. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical advice or attention. Take off contaminated clothing and wash it before reuse. Use only outdoors or in a well-ventilated area. Avoid breathing fumes, vapors and sprays. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell. If swallowed: Immediately call a poison center or doctor. Do NOT induce vomiting. Dispose of contents and container in accordance with local, state, and federal regulations.

SYMBOL:



HAZARDS NOT OTHERWISE CLASSIFIED: N/A

SECTION III – COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENT	CAS NUMBER	PERCENT
Heptane	142-82-5	20-30%
Propane	74-98-6	10-30%
Butane	106-97-8	10-30%
trans-1,2-Dichloroethylene	156-60-5	1-10%

Trade Secret Information: A specific chemical identity and/or percentage of composition has been withheld as a trade secret.

SECTION IV - FIRST AID MEASURES

EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.
INGESTION: Rinse mouth out with water. Do not induce vomiting unless directed by medical authority. Seek medical attention if irritation persists. Never give anything by mouth to an unconscious person.
INHALATION: Remove to fresh air. If not breathing administer artificial respiration. If breathing is difficult give oxygen. Consult a physician.
SKIN: Remove contaminated clothes. Wash skin thoroughly with soap and water for 15 minutes. Seek medical attention if irritation develops. Wash contaminated clothing before reuse.

Safety Data Sheet

PREP-A-LUBE II

ACUTE HEALTH HAZARDS: Contact with eyes may cause irritation, redness, tearing. Causes skin irritation including redness, burning and drying/cracking. Inhalation of vapors may cause nausea, dizziness and drowsiness. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

CHRONIC HEALTH HAZARDS: Dermatitis may occur due to long-term irritation.

NOTE TO PHYSICIAN: Treatment of overexposure should be directed at the control of symptoms and the clinical condition.

SECTION V – FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA: Dry chemical, carbon dioxide, foam, and water spray or fog.

UNSUITABLE EXTINGUISHING MEDIA: Water spray/stream.

SPECIAL FIRE FIGHTING PROCEDURES: Wear NIOSH approved Self-Contained Breathing Apparatus with a full-face piece operated in a positive pressure demand mode with full body protective clothing when fighting fires. Shut off all sources of ignition. Use water spray to disperse vapor and cool fire exposed containers. Prevent run off from entering streams, sewers, or drinking water supply.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Contents under pressure. Exposure to temperatures above 120 °F may cause bursting. Vapors heavier than air will settle in low lying areas and may travel to source of ignition and flash-back. Keep away from heat, sparks, open flames and other sources of ignition.

HAZARDOUS COMBUSTION PRODUCTS: Oxides of carbon, aldehydes, various hydrocarbons.

SECTION VI – ACCIDENTAL RELEASE MEASURES

PERSONAL PROTECTIVE EQUIPMENT: Refer to section VIII for proper Personal Protective Equipment.

SPILL: Eliminate all sources of ignition. Clean up using rag or use some non-combustible material like vermiculite, sand or earth. Prevent spill from entering sewers, storm drains and natural waterways. Place waste in proper containers for disposal.

WASTE DISPOSAL: Dispose of in accordance with local, state and federal regulations. Do not dump in sewers.

RCRA STATUS: Waste likely considered D001 (Ignitable waste), under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

SECTION VII – HANDLING AND STORAGE

HANDLING AND STORAGE: Do not use or store near heat, open flames or other sources of ignition. Wear proper personal protective equipment when using this product. Avoid contact with skin, eyes and clothing. Do not inhale mist or vapor. Do not use or store with strong oxidizers. Protect from sunlight. Store in a well-ventilated area. Do not expose to temperatures exceeding 50 °C/122 °F. Pressurized container: Do not pierce or burn, even after use. Store in a cool, dry area.

OTHER PRECAUTIONS: Keep out of the reach of children. Read and follow the directions on the product label. They are the best guide to using the product in the most effective manner. The label also gives you the necessary safety precautions to protect your health.

INCOMPATIBILITY: Strong oxidizing agents, strong reducing agents.

SECTION VIII – EXPOSURE CONTROLS/PERSONAL PROTECTION

HAZARDOUS INGREDIENT	OSHA PEL	ACGIH TLV
Heptane	500 ppm	50 ppm
Propane	1000 ppm	1000 ppm
Butane	Not Established	1000 ppm
trans-1,2-Dichloroethylene	Not Established	200 ppm

ENGINEERING CONTROLS / VENTILATION: Material is heavier than air. Material may concentrate in low lying areas. Normal, forced ventilation required to meet TLV requirements. Local exhaust ventilation is generally preferred.

RESPIRATORY PROTECTION: Not required with adequate ventilation. Wear NIOSH/MSHA approved respiratory protection if exposure limits are exceeded.

PERSONAL PROTECTIVE EQUIPMENT: Safety glasses/goggles and chemical resistant gloves.

ADDITIONAL MEASURES: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid contact with skin or eyes and avoid breathing vapors. Wash hands after use.

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Opaque red spray

ODOR: Solvent odor.

ODOR THRESHOLD: N/D

pH: N/A

MELTING POINT/FREEZING POINT: N/D

Safety Data Sheet
PREP-A-LUBE II

INITIAL BOILING POINT AND BOILING RANGE: N/D
FLASH POINT: N/D
EVAPORATION RATE: N/D
FLAMMABILITY (solid/gas): Extremely flammable aerosol.
UPPER/LOWER FLAMMABILITY OR EXPLOSIVE LIMITS:
LOWER FLAMMABILITY LIMIT: N/D
UPPER FLAMMABILITY LIMIT: N/D
EXPLOSIVE LIMIT LOWER (%): N/D
EXPLOSIVE LIMIT UPPER (%): N/D
VAPOR PRESSURE (mm Hg): N/D
VAPOR DENSITY (AIR=1): N/D
RELATIVE DENSITY (H₂O=1): 0.83 - 0.87 @77 °F (25 °C)
SOLUBILITY(IES): N/D
PARTITION COEFFICIENT: n-OCTANOL/WATER (K_{ow}): N/D
AUTOIGNITION TEMPERATURE: N/D
DECOMPOSITION TEMPERATURE: N/D
VISCOSITY: N/D

SECTION X – STABILITY AND REACTIVITY

REACTIVITY: None known.
CHEMICAL STABILITY: Stable.
POSSIBLE HAZARDOUS REACTIONS: None known.
CONDITIONS TO AVOID: Temperatures greater than 122 °F (50 °C) and sources of ignition. Avoid incompatible materials.
INCOMPATIBLE MATERIALS: Strong oxidizing agents, strong reducing agents.
HAZARDOUS DECOMPOSITION PRODUCTS: None known.

SECTION XI – TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION: **Heptane** (142-82-5): LD₅₀ (Oral, Rat) > 15000 mg/kg; LD₅₀ (Dermal, Rabbit) > 3160 mg/kg; LC₅₀ (Inhalation, Rat, 4h) 103 mg/L. **trans-1,2-Dichloroethylene** (156-60-5): LD₅₀ (Oral, Rat) 1235 mg/kg; LD₅₀ (Dermal, Rabbit) >5000 mg/kg; LC₅₀ (Inhalation, Rat, 4h) 24100 ppm. **Propane** (74-98-6): LC₅₀ (Inhalation, Rat, 4h) 658 mg/L. **Butane** (106-97-8): LC₅₀ (Inhalation, Rat, 4h) 30957 mg/m³.
ROUTES OF ENTRY: Eyes, Ingestion, Inhalation, Skin
EYES: May cause burning, irritation, redness, tearing.
INGESTION: Aspiration hazard. Can enter the lungs during swallowing or vomiting and cause chemical pneumonia or edema. May cause gastrointestinal irritation, nausea, diarrhea, vomiting.
INHALATION: May cause respiratory tract irritation, dizziness, headaches, nausea, unconsciousness, central nervous system (CNS) depression.
SKIN: Irritation likely, redness and pain. May cause localized defatting, blistering with prolonged skin contact. May be absorbed through the skin.
MEDICAL CONDITION AGGRAVATED: Excessive exposure will aggravate pre-existing disorders of eyes, skin, respiratory, liver, kidney, cardiovascular system, pulmonary illnesses, or central nervous system (CNS).
ACUTE HEALTH HAZARDS: Contact with eyes may cause irritation, redness, tearing. Causes skin irritation including redness, burning and drying/cracking. Inhalation of vapors may cause nausea, dizziness and drowsiness. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.
CHRONIC HEALTH HAZARDS: Dermatitis may occur due to long-term irritation.
CARCINOGENICITY: OSHA: No ACGIH: No NTP: No IARC: No OTHER: N/A

SECTION XII – ECOLOGICAL INFORMATION

ECOTOXICITY: Toxic to aquatic life with long lasting effects. Avoid release to the environment.
PERSISTENCE AND DEGRADABILITY: Not readily biodegradable.
BIOACCUMULATIVE POTENTIAL: Components in this mixture can bioaccumulate in aquatic organisms.
MOBILITY IN SOIL: N/D
OTHER ADVERSE EFFECTS: None known.

SECTION XIII – DISPOSAL CONSIDERATIONS

WASTE DISPOSAL: Dispose of in accordance with local, state and federal regulations. Do not dump in sewers.
RCRA STATUS: Waste likely considered D001 (Ignitable waste), under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

Safety Data Sheet
PREP-A-LUBE II

SECTION XIV - TRANSPORT INFORMATION

PROPER SHIPPING NAME: Aerosols, Ltd. Qty.
HAZARD CLASS/DIVISION: 2.1
UN/NA NUMBER: UN1950
PACKING GROUP: N/A

AIR SHIPMENT

PROPER SHIPPING NAME: Aerosols, flammable.
HAZARD CLASS/DIVISION: 2.1
UN/NA NUMBER: UN1950
PACKING GROUP: N/A

SHIPPING BY WATER:

VESSEL (IMO/IMDG)

PROPER SHIPPING NAME: Aerosols.
HAZARD CLASS/DIVISION: 2.1
UN/NA NUMBER: UN1950
PACKING GROUP: N/A

ENVIRONMENTAL HAZARDS WATER: Marine Pollutant.

SECTION XV - REGULATORY INFORMATION

TSCA STATUS: All chemicals are listed or exempt.

CERCLA (COMPREHENSIVE RESPONSE COMPENSATION, AND LIABILITY ACT): **Trans-Dichloroethylene** Reportable
Quantity = 1470 pounds (based on the percentage composition of this chemical in the product)

SARA 311/312 HAZARD CATEGORIES: Flammable (gases, aerosols, liquids, solids). Gas under pressure. Skin corrosion or irritation. Reproductive toxicity. Specific target organ toxicity (single or repeated exposure).

SARA 313 REPORTABLE INGREDIENTS: **trans-1,2 Dichloroethylene** (156-60-5).

STATE REGULATIONS: California Proposition 65: This product does not contain chemicals as regulated by California Proposition 65. **Heptane** (142-82-5): Included on State Hazardous Substances Inventories, Right-to-Know lists and/or Air Quality or Air Pollutants lists for the following states: CA, IL, MA, NJ, PA, RI.

INTERNATIONAL REGULATIONS: Heptane (142-82-5): Listed or exempted on inventory list for Australia, Canada, China, Europe, Japan, South Korea, New Zealand, Philippines, Switzerland, Taiwan. **Propane (74-98-6):** Listed or exempted on the AICS (Australian Inventory of Chemical Substances), Canadian DSL (Domestic Substances List), IECSC (Inventory of Existing Chemical Substances Produced or Imported in China), EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances), Japanese ENCS (Existing & New Chemical Substances), Korean ECL (Existing Chemicals List), NZIoC (New Zealand Inventory of Chemicals), and PICCS (Philippines Inventory of Chemicals and Chemical Substances). **trans-1,2-Dichloroethylene (156-60-5):** Listed or exempted on the AICS (Australian Inventory of Chemical Substances), Canadian DSL (Domestic Substances List), IECSC (Inventory of Existing Chemical Substances Produced or Imported in China), EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances), Japanese ENCS (Existing & New Chemical Substances), Korean ECL (Phase-in substance; KE-10123), NZIoC (New Zealand Inventory of Chemicals), and PICCS (Philippines Inventory of Chemicals and Chemical Substances).

Butane (106-97-8): Listed or exempted on the AICS (Australian Inventory of Chemical Substances), Canadian DSL (Domestic Substances List), IECSC (Inventory of Existing Chemical Substances Produced or Imported in China), EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances), Japanese ENCS (Existing & New Chemical Substances), Korean ECL (Existing Chemicals List), NZIoC (New Zealand Inventory of Chemicals), and PICCS (Philippines Inventory of Chemicals and Chemical Substances).

VOLATILE ORGANIC COMPOUNDS (VOC): 71.2%

NFPA HEALTH: 3

NFPA FLAMMABILITY: 4

NFPA REACTIVITY: 0

NFPA OTHER: None

HMIS HEALTH: 3

HMIS FLAMMABILITY: 4

HMIS REACTIVITY: 0

HMIS PROTECTION: B

SECTION XVI - OTHER INFORMATION

PREPARATION BY: Technical Services

DATE PREPARED: 05/04/2026

REVISION DATE: 05/04/2026

Safety Data Sheet
PREP-A-LUBE II

N/A = Not Applicable; N/D = Not Determined

DISCLAIMER: To the best of our knowledge, information contained herein is accurate. However, there is no assumption of liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist. The information contained in this SDS was obtained from current and reliable sources; however, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions of handling, storage and disposal of this product are beyond the control of the manufacturer, the manufacturer will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this SDS shall be created or inferred by any statement in this SDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this SDS. The user is responsible for full compliance.

. . . END of SDS . . .