

Product Data

SUPER VINDICATOR

Enzymatic Grease Buster

Places of Uses:

- Storage Tanks
- Oil Refineries
- Lift Stations
- Hospitals
- Factories
- Septic Systems
- Automotive Repair Shops
- Sand or Mixed Media Tertiary Filters
- Waste Water Treatment Plants
- Marine Applications
- Steam Cleaners and Much More

SUPER VINDICATOR is a unique bacteria-free blend of proprietary agents which cut through and lift grease, oil and other hydrocarbons. **SUPER VINDICATOR** is used to remove petroleum distillates without emulsifying. It causes the release and separation of crude and refined oils, as well as hydrocarbons, at temperatures from near freezing to near boiling. This separation then allows the recovery, reuse, or disposal of the hydrocarbon components.

- ✓ Non-Emulsifying
- ✓ Highly Dilutable
- ✓ Broad Temperature Range Application
- ✓ Contains Lipase Enzyme
- ✓ A Unique Bacteria-Free Pre-Degreaser



...setting performance
standards worldwide...

APPLICATIONS

SUPER VINDICATOR is used to remove crude petroleum and petroleum distillates from many surfaces. SUPER VINDICATOR does not emulsify when used as directed, however, it causes the lifting and separation of crude and refined hydrocarbons from soil, machinery, exchangers, storage tanks and other surfaces. While using natural enzymes, SUPER VINDICATOR dissipates grease, hydrocarbons, organics and hydrogen sulfide gas odor. It is safe for drains, septic systems, sinks, grease traps, lift stations, aeration tanks, sand or mixed media tertiary filters, refinery columns, engine rooms and flexicoker and heat exchangers.

DIRECTIONS

Grease or oil in aeration tanks: Aids in settling... Mix 20,000-40,000:1 SUPER VINDICATOR. **For digester cleaning:** Use at 40:1 in a pressure washer. **For sand or mixed media tertiary filters:** Use 100:1 for anthracite and 200:1 for sand filters. **For lift stations:** Use at 500:1 to pre-degrease and clean. **For refinery columns, flexicoker and heat exchangers:** Use at 40:1 for column and line cleaning. **For bilges:** Use at 30:1 with a pressure washer. **For engine rooms:** Use at 10:1 for bucket and brush cleaning or 30:1 with a pressure washer. **For problem areas:** Use at full strength. **For drains:** Add one quart and allow to sit for 20 minutes. Flush with hot water for several minutes. **For maintenance dose:** Add 4 to 8 oz to each drain each week. **For general cleaning:** Mix 20 to 30 parts water with one part SUPER VINDICATOR.

TECHNICAL DATA

Active Ingredients: Lipase Enzyme, surfactants,
alkaline builders
Specific Gravity: 1.002
Solubility in Water: Complete
pH: 11.0 - 12.0
Appearance: Clear green liquid
Odor: Characteristic
**Supplemental
Product:** DEVOUR



...setting performance
standards worldwide...

C-9,15/PC-6522/0325